

Glass tape especially suited for large motors and engines meeting high demands of the thermal class. The surface layer of the tape is coated with Amino Silane to promote good absorption of varnishes and resins. Dimensionally stable



### Typical applications

Suitable for the binding of solenoids, field coils and coil ends in electric motors as well as electrical applications.

### Properties

- Good resistance to chemicals
- Working temperature 220°C, intermittent 500°C
- Good rigidity
- High tensile strength
- High varnish and resin absorption capacity

### Composition

Woven glass tape coated with Amino Silane

### Colour

White

### Technical data

- Temperature class 220°C, intermittent +500°C
- Max elongation: 30 N/mm
- Tolerance on width:  $\pm 1$  mm
- Weight  $g/m^2$ : 143
- Thickness:  $0.13 \pm 0.025$  mm

Item number	Dimensions (mm)	Packaging
125727	0.13 x 25	50 m / roll
125723	0.13 x 38	100 m / roll
125725	0.13 x 38	280 m / roll
125728	0.13 x 38	50 m / roll

### How to contact BEVI

Contact details for all countries are continually updated on our website. Please visit [www.bevi.com](http://www.bevi.com) to access the information direct.

BEVI AB (Headquarters)  
Blomstermåla, Sweden  
Tel. +46 499 271 00  
[info@bevi.se](mailto:info@bevi.se)